

# Mini Fogger II™

At a full 1000 watts, there is nothing "mini" about the longer output of this new economical fog machine. Perfect for small venues, it includes an on/off remote. Metal body, shop tested, reliable, with longer output time than our previous model.



## Specifications

120VAC P/N 100081, 230VAC P/N 100084

Type of Fog: Water-based fog

Weight: 10 lbs / 4.5 kg

Dimensions: 15" x 12" x 12"  
(38 cm x 30 cm x 30 cm)

Shipping Weight: 11 lbs. (5 kg)

Shipping Box Size: 18" x 13" x 13"  
(46 cm x 33 cm x 33 cm)

Fogging Fluid: CITC Natural Fogging Fluid™ Regular P/N 150410 or Long-lasting P/N 150450

Fluid Capacity: 26 oz (0.77 liter)

Warm Up Time: 7-10 minute initial, 2 min. intermittent

Fog Output: 5000 CFM for one minute, reheat 2 min., then another one-minute cycle

Heating unit: 1000 W

Electrical Supply: 120 VAC, 10 A, 60 Hz  
230 VAC, 6 A, 50 Hz


Fuse: 10 amp – 250v (120v machine)

6 amp-250v (230v machine)

Limited Warranty: 90 days



European Distributorship:  
White Light Ltd. UK  
Sales@WhiteLight.Ltd.uk

 [www.facebook.com/CITCFX](http://www.facebook.com/CITCFX)

(888) 786-CITC (425) 776-4950 [info@citcfx.com](mailto:info@citcfx.com) [www.citcfx.com](http://www.citcfx.com) Everett, WA USA