

# Super Foam Dome™

The new Super Foam Dome is a 1hp foam machine with a 25' (8m) electric cord and GFCI switched plug, high pressure pump, extra large modulator, 25' (8m) connecting tubing, safety cable, safety goggles, and safety banner. All that's needed is a barrel for adding the fluid to 50 gallons (189l) of warm water. Uses less fluid per CFM of foam fluid than the original Foam Dome. Fill a 20' x 20' x 6' (51 cm x 51 cm x 15 cm) area within 6 minutes.



## Specifications

120V P/N #100216

Dimensions: 19" x 19" x 19" (48cm x 48cm x 48cm)

Weight: 28 lbs (12 kg) (plus pump: see below)

Power: 1 hp: 120 VAC, 60 Hz, 20 A

Power Cord: 25' (7.6 m)

GFI switch box: Two outlets with lighted power switch

GFI Power Cord: 8' (2.5m)

Fluid pump: High-pressure diaphragm pump 45 psi (3.1 bar) / 1.4gpm (5.3 lpm)

Wt/Dims fluid pump: 5lbs (2.3 kg) / 7"x5"x5" (18x13x13cm)

Pump Power: 120 VAC, 60 Hz, 0.7 A

Pump Power Cord: 6ft (1.8 m)

Type of Fluid: Super Foam Dome™ fluid/water mix

Output: 500 cubic feet per minute (14m<sup>3</sup>/min)

Fluid Consumption: Approx 1 gallon per minute (3.8 l/min)

Hose: 5/8" x 25' (1cm x 7.6m) plastic

Barrel supplied by user: 55gal (209 liter) plastic

Limited Warranty: One year



European Distributorship:

White Light Ltd. UK

Sales@WhiteLight.Ltd.uk



[www.facebook.com/CITCFX](http://www.facebook.com/CITCFX)

(888) 786-CITC (425) 776-4950 [info@citcfx.com](mailto:info@citcfx.com) [www.citcfx.com](http://www.citcfx.com) Everett, WA USA